Dangerous Goods	Location			Restrictions	
Durige out Coole	Checked baggage Carry-on baodage		Approval of the operator(s) is required		
Batteries				1	
 Lithium batteries (including portable electronic devices) 	Yes (except for g) and h))	Yes	(see c) and d))	a)	each battery must be of a type which meets the requirement of each test in the UN <i>Manual of Tests and Criteria</i> , Part II subsection 38.3;
				b)	each battery must not exceed the following:
					- for lithium metal batteries, a lithium content of 2 grams; or
					— for lithium ion batteries, a Watt-hour rating of 100 Wh;
				c)	each battery may exceed 100 Wh but not exceed 160 Wh Wa hour rating for lithium ion with the approval of the operator;
				d)	each battery may exceed 2 grams but not exceed 8 gran lithium content for lithium metal for portable medical electron devices with the approval of the operator;
				e)	batteries contained in portable electronic devices should carried as carry-on baggage; however, if carried as check baggage:
					 measures must be taken to prevent unintentional activation and to protect the devices from damage; and
					 the devices must be completely switched off (not in sleep or hibernation mode);
				f)	batteries and heating elements must be isolated in portal electronic devices capable of generating extreme heat, whi could cause a fire if activated, by removal of the heati element, battery or other components;
				g)	spare batteries, including power banks:
					 must be carried as carry-on baggage; and
					 must be individually protected so as to prevent sh circuits (by placement in original retail packaging or otherwise insulating terminals, e.g. by taping ov exposed terminals or placing each battery in a separa plastic bag or protective pouch);
				h)	baggage equipped with a lithium battery(ies) exceeding:
					 for lithium metal batteries, a lithium content of 0.3 gram or
					— for lithium ion batteries, a Watt-hour rating of 2.7 Wh
					must be carried as carry-on baggage unless the battery(ies) removed from the baggage, in which case the battery(ies) mill be carried in accordance with g);
				i)	no more than two spare batteries meeting the requirements c) or d) may be carried per person.

	Dangerous Goods	Loc	ation		Restrictions
		Checked baggage	Carry-on baggage	Approval of the operator(s) is required	
2)	Non-spillable batteries	Yes	Yes	No	a) must meet the requirements of Special Provision A67;
					b) each battery must not exceed a voltage of 12 volts and a Watt- hour rating of 100 Wh;
					c) each battery must be protected from short circuit by the effective insulation of exposed terminals;
					d) no more than two spare batteries per person may be carried and
					 e) if contained in equipment, the equipment must be eithe protected from unintentional activation, or each battery mus be disconnected and its exposed terminals insulated.
3)	Battery-powered portable electronic	No	Yes	No	 a) if powered by lithium batteries, each battery must comply with restrictions of 1) a), b) and g);
	smoking devices (e.g. e-cigarettes, ecigs, ecigars, epipes, personal				b) the devices and/or batteries must not be recharged on board the aircraft; and
	vaporizers, electronic nicotine delivery systems)				c) measures must be taken to prevent unintentional activation of the heating element while on board the aircraft.
4)	Battery-powered mobility aids (e.g. wheelchairs)	Yes (see d))	Yes	 a) for use by passengers whose mobility is restricted by either a disability, their health or age, or a temporary mobility problem (e.g. broken leg); 	
					b) the passenger should make advance arrangements with each operator and provide information on the type of batter installed and on the handling of the mobility aid (including instructions on how to isolate the battery);
					c) in the case of a non-spillable wet battery:
					 i) each battery must comply with Special Provision A67; and
					ii) a maximum of one spare battery may be carried per passenger;
					d) in the case of a lithium ion battery:
					 i) each battery must be of a type which meets the requirement of each test in the UN Manual of Tests and Criteria, Par III, subsection 38.3;
					ii) when the mobility aid does not provide adequate protection to the battery:
					 — the battery must be removed in accordance with the manufacturer's instructions;
					- the battery must not exceed 300 Wh;
					 the battery terminals must be protected from sho circuit (by insulating the terminals, e.g. by taping ove exposed terminals);
					 — the battery must be protected from damage (e.g. by placing each battery in a protective pouch); and
					— the battery must be carried in the cabin;
					iii) a maximum of one spare battery not exceeding 300 Wh o two spare batteries not exceeding 160 Wh each may be carried. Spare batteries must be carried in the cabin.

	Dangerous Goods	Location			Restrictions
	Ĵ	Checked baggage	Carry-on baggage	Approval of the operator(s) is required	
es and f	fuel sources				
5)	Cigarette lighter	No	(see b))	No	a) no more than one per person;
	Small packet of safety				b) must be carried on the person;
	matches				c) must not contain unabsorbed liquid fuel (other than liquefied gas); and
					 d) if a cigarette lighter is powered by lithium batteries, each battery must comply with restrictions of 1) a), b) and g) a 3) b) and c).
6)	Alcoholic beverages	Yes	Yes	No	a) must be in retail packagings; and
	containing more than 24 per cent but not more				b) no more than 5 L total net quantity per person.
	than 70 per cent alcohol by volume				Note.— Alcoholic beverages containing not more than 24 p cent alcohol by volume are not subject to any restrictions.
7)	Internal combustion engines or fuel cell engines	Yes	No	No	Measures must be taken to nullify the hazard. Refer to Special Provision A70 for more information.
8)	Fuel cells containing fuel	No	Yes	No	 a) fuel cell cartridges may only contain flammable liquids, corros substances, liquefied flammable gas, water reac substances or hydrogen in metal hydride;
	Spare fuel cell cartridges	l cartridges Yes	Yes	No	 b) refuelling of fuel cells on board an aircraft is not permitted except that the installation of a spare cartridge is allowed;
					c) the maximum quantity of fuel in any fuel cell or fuel cell cartridge must not exceed:
					— for liquids 200 mL;
					— for solids 200 grams;
					 for liquefied gases, 120 mL for non-metallic fuel cartridges or 200 mL for metal fuel cell or fuel cartridges; and
					 for hydrogen in metal hydride, the fuel cell or fuel cell cartridges must have a water capacity of 120 mL or le
					 d) each fuel cell and each fuel cell cartridge must conform to 62282-6-100 Ed. 1, including Amendment 1, and must marked with a manufacturer's certification that it conforms the specification. In addition, each fuel cell cartridge must marked with the maximum quantity and type of fuel in cartridge;
					 e) fuel cell cartridges containing hydrogen in metal hydride mus comply with the requirements in Special Provision A162;
					f) no more than two spare fuel cell cartridges may be carried b a passenger;

	Dangerous Goods	Location			Restrictions		
		Checked baggage Carry-on	Carry-on baggage	Approval of the operator(s)			
					g) fuel cells containing fuel are permitted in carry-on baggage only;		
					 h) interaction between fuel cells and integrated batteries in a device must conform to IEC 62282-6-100 Ed. 1, including Amendment 1. Fuel cells whose sole function is to charge a battery in the device are not permitted; 		
					 fuel cells must be of a type that will not charge batteries wher the portable electronic device is not in use and must be durably marked by the manufacturer: "APPROVED FOR CARRIAGE IN AIRCRAFT CABIN ONLY" to so indicate; and 		
					in addition to the languages which may be required by the State of Origin for the markings specified above, English should be used.		
in cylir	nders and cartridges			1			
9)	Cylinders of oxygen or air required for medical	Yes	Yes	Yes	a) no more than 5 kg gross mass per cylinder;		
	use				b) cylinders, valves and regulators, where fitted, must b protected from damage which could cause inadvertent release of the contents;		
					c) advance arrangements recommended; and		
					 the pilot-in-command must be informed of the number or oxygen or air cylinders loaded on board the aircraft and their loading location(s). 		
10)	Cartridges of Division 2.2 worn for the operation of mechanical limbs	Yes	Yes	No	Spare cartridges of a similar size are also allowed, if required, to ensure an adequate supply for the duration of the journey.		
11)	Cartridge of hydrocarbon	Yes	Yes	No	a) no more than one per person;		
	gas contained in hair styling equipment				b) the safety cover must be securely fitted over the heating element; and		
					c) spare cartridges must not be carried.		
12)	Cartridges of	Yes	Yes	Yes	a) no more than one personal safety device per person;		
	Division 2.2 with no subsidiary hazard fitted into a self-inflating				b) the personal safety device must be packed in such a manner that it cannot be accidentally activated;		
	personal safety device such as a life-jacket or				c) must be for inflation purposes;		
	vest				d) no more than two cartridges are fitted into the device; and		
					e) no more than two spare cartridges.		
13)	Cartridges of	Yes	Yes	Yes	a) no more than four cartridges per person; and		
	Division 2.2 with no subsidiary hazard for other than a self-inflating				b) the water capacity of each cartridge must not exceed 50 mL.		
	personal safety device				Note.— For carbon dioxide, a gas cartridge with a water capacity of 50 mL is equivalent to a 28 g cartridge.		

	Dangerous Goods	Location			Restrictions
	Dangorous Coold	Checked baggage	Carry-on baggage	Approval of the operator(s) is required	
14)	Cartridges and cylinders of Division 2.2 with no subsidiary hazard contained in an avalanche rescue backpack	Yes	Yes	Yes	 a) no more than one avalanche rescue backpack per person; b) the backpack must be packed in such a manner that it cannot be accidentally activated; c) may contain a pyrotechnic trigger mechanism which must not contain more than 200 mg net of Division 1.4S; and d) the airbags within the backpack must be fitted with pressure relief valves.
Radioactive r	material		I		
15)	Radioisotopic cardiac pacemakers or other medical devices	n/a (see restrictions)	n/a (see restrictions)	No	Must be implanted into a person or fitted externally as the result of medical treatment.
Mercury					
16)	Small medical or clinical thermometer which contains mercury	Yes	No	No	a) no more than one per person; andb) must be in its protective case.
Other danger	,				
17)	Non-radioactive medicinal articles	Yes	Yes	No	a) no more than 0.5 kg or 0.5 L total net quantity per single article;
	(including aerosols), toiletry articles (including aerosols) and aerosols in Division 2.2 with no subsidiary hazard				 b) no more than 2 kg or 2 L total net quantity of all articles (e.g. four aerosol cans of 0.5 L each) per person; c) release valves on aerosols must be protected by a cap or other suitable means to prevent inadvertent release of the contents; and d) the release of gas must not cause extreme annoyance or discomfort to crew members so as to prevent the correct performance of assigned duties.
18)	Dry ice	Yes	Yes	Yes	a) no more than 2.5 kg per person;
					b) used to pack perishables that are not subject to these Instructions;
					c) the package must permit the release of carbon dioxide gas; and
					d) when carried as checked baggage, each package must be marked:
					i) "DRY ICE" or "CARBON DIOXIDE, SOLID"; and
					the net weight of dry ice or an indication that the net weight is 2.5 kg or less.
19)	Cartridges in Division 1.4S	Yes	No	Yes	a) no more than 5 kg gross mass per person;
	(UN 0012 or UN 0014				b) must be securely packaged;
	only)				c) must not include ammunition with explosive or incendiary projectiles; and
					 allowances for more than one person must not be combined into one or more packages.

	Dangerous Goods	Loca	ation		Restrictions
	Dangerous Goods	Checked baggage	Carry-on baggage	Approval of the operator(s) is required	Restructions
20)	Permeation devices	Yes	No	No	Instructions on how to package permeation devices for calibrating air quality monitoring equipment are found in Special Provision A41.
21)	Non-infectious specimens in flammable solutions	Yes	Yes	No	Instructions on how to package and mark specimens are found in Special Provision A180.
22)	Refrigerated liquid nitrogen	Yes	Yes	No	Must be contained in insulated packagings (e.g. dry shippers) that would not allow the build-up of pressure and be fully absorbed in a porous material so that there is no free liquid that could be released from the packaging. Refer to Special Provision A152 for more information.
23)	Dangerous goods incorporated in security- type equipment, such as attaché cases, cash boxes, cash bags, etc.	Yes	No	Yes	The security-type equipment must be equipped with an effective means of preventing accidental activation and the dangerous goods incorporated in the equipment must meet the conditions of Special Provision A178.

Table 8-2. Provisions for instruments carried by OPCW and government agencies2019 - 2020

	Dangerous goods	Location			Restrictions
	Dangerous goous	Checked baggage	Carry-on baggage	Approval of the operators is required	Nesulcions
1)	Instruments containing radioactive material (i.e. chemical agent monitor (CAM) and/or rapid alarm and identification device monitor (RAID-M))	Yes	Yes	Yes	 a) the instruments must not exceed the activity limits specified in Table 2-14 of these Instructions; b) must be securely packed; and c) must be carried by staff members of the Organization for the Prohibition of Chemical Weapons (OPCW) on official travel.
2)	A mercurial barometer or mercurial thermometer	No	Yes	Yes	 a) must be carried by a representative of a government weather bureau or similar official agency; b) must be packed in a strong outer packaging, having a sealed inner liner or a bag of strong leakproof and puncture-resistant material impervious to mercury, which will prevent the escape of mercury from the package irrespective of its position; and c) the pilot-in-command must be informed of the barometer or thermometer.